

JVC

The Perfect Experience / —



TH-C30
DVD Digital Theater System

Product Description

1,000W Mega Power DVD-Audio/Video Theater System with 5-Disc Changer and Omni-Directional Surround Speakers -- featuring Progressive Scan Compatibility, USB Hosting and DivX

Basic Features

- 5-Disc Changer
- Dolby Digital, DTS and Dolby Pro Logic II Decoders Built-in
- Power Output: Front/Center/Surround: 167 watts per channel*; Subwoofer: 167 watts**
- Playable Formats: DVD-Audio, DVD-Video, DVD-RW, DVD-R, +RW, +R, CD, CD-R/RW, SVCD/VCD, MP3/WMA/JPEG Digital Still (CD-R/RW, DVD-R/RW), MPEG-4 (ASP)/DivX (CD-R/RW, DVD-R/RW)

- Progressive Scan Output
- USB Host (2.0 Full-Speed)
- Component Video Output
- Digital (Optical) Audio Input

* min. RMS, driven into 3 ohms at 1kHz, with no more than 10% total harmonic distortion

** min. RMS, driven into 3 ohms at 100Hz, with no more than 10% total harmonic distortion

Product Highlights

- 5-Disc Changer Digital Theater System with 1,000W Mega Power
- Digital Direct Progressive Scan Output
- Digital Surround Mode for 2ch Sound: Dolby Pro Logic II (Movie/Music)/All Channel Stereo/Stadium
- USB Host Function
- DVD Express Play Start
- 192kHz/24-bit Audio D/A Converter
- 12-bit/108MHz Video D/A Converter
- Omni-Directional Surround Speakers for a wider sound field and realistic acoustic ambience
- 2-Way Speakers (Front/Center)
- Wall-Mountable Speakers (Front/Center/Surround)
- 6-5/16" (16cm) Powered Subwoofer
- Multi-Brand Remote Control (TV/VCR)

General Specifications

Circuitry:

- Video D/A Converter (12-bit/108MHz) • Audio D/A Converter (192kHz/24-bit) • Dolby Digital Decoder • DTS Decoder • Dolby Pro Logic II Decoder • All Channel Stereo Mode • Stadium Mode for 2ch TV Sound

DVD Functions:

- DVD Express Play Start • Rolling Pickup • VFP (Video Fine Processor) • Variable Search (Forward/Reverse) • Variable Slow (Forwarded/Reverse) • One-Touch Replay • Resume Function • Zoom Play

Tuner:

- AM/FM Digital Tuner • Number of Presets (30FM/15AM)

Terminals:

- Analog Audio In • Digital (Optical) Audio In • Composite Video In/Out • S-Video In/Out • Component Video Out • USB Host • Headphone Out • AV COMPU LINK

On-Screen Language:

- English/French/Spanish

Subwoofer:

- 167 watts min. RMS, driven into 3 ohms at 100Hz, with no more than 10% total harmonic distortion • Bass Reflex (6 5/16" (16cm) Cone) • Powered

Front Speakers (Magnetically Shielded):

- 167 watts per channel, min. RMS, driven into 3 ohms at 1kHz, with no more than 10% total harmonic distortion • 2 Way, 2 Speaker Bass Reflex (3 3/16" (8cm) Cone, 5/8" (1.5cm) Dome) • Frequency Range (80Hz - 20kHz) • Wall Mountable

Center Speaker (Magnetically Shielded):

- 167 watts, min. RMS, driven into 3 ohms at 1kHz, with no more than 10% total harmonic distortion • 2 Way, 2 Speaker Bass Reflex (3 3/16" (8cm) Cone, 5/8" (1.5cm) Dome) • Frequency Range (80Hz - 20kHz) • Wall Mountable

Surround Speakers (Magnetically Shielded):

- 167 watts per channel, min. RMS, driven into 3 ohms at 1kHz, with no more than 10% total harmonic distortion • 1 Way, Full Range, Bass Reflex (3 3/16" (8cm) Cone) • Frequency Range (80Hz - 20kHz) • Wall Mountable

Details, Weights & Measurements

Center Unit:

- Dimensions (WxHxD) inches: 15 3/4 x 3 3/8 x 12 1/2
- Approximate Weight (lbs./kg): 8.4/3.8

Front Speakers:

- Dimensions (WxHxD) inches: 4 1/8 x 5 1/2 x 4
- Approximate Weight (lbs./kg): 1.3/0.56

Center Speaker:

- Dimensions (WxHxD) inches: 5 7/16 x 4 3/16 x 4 1/8
- Approximate Weight (lbs./kg): 1.3/0.57

Surround Speakers:

- Dimensions (WxHxD) inches: 4 7/16 x 5 7/8 x 4 1/4
- Approximate Weight (lbs./kg): 1.4/0.56

Subwoofer:

- Dimensions (WxHxD) inches: 6 3/4 x 16 3/16 x 18 1/16
- Approximate Weight (lbs./kg): 25.4/11.5



DISTRIBUTED BY

JVC COMPANY OF AMERICA
A Division of JVC Americas Corp.
1700 Valley Road, Wayne, NJ 07470
www.jvc.com

"JVC" is the trademark of Victor Company of Japan, Limited