Spec

Specifications

AV Navigation Systems

Navigation System	KW-NT3HDT	KW-NT3HD
Type	On-Board Flash Memory Based Navigation System	On-Board Flash Memory Based Navigation System
GPS	✓ (WAAS Capable)	✓ (WAAS Capable)
Speed Pulse	V (WAS ORDERS)	V (WANG GARAGIC)
Gyro Sensor	V	V
Coverage	United States, Alaska, Hawaii, Canada, and Puerto Rico	United States, Alaska, Hawaii, Canada, and Puerto Rice
StreetDirector Assistant	V	V
HD Radio® Traffic & News Service	V	
Destination Search Functions	Name, Vicinity, Phone Number, Address, Zip-Code, Coordinates, Previous, Favorites, User P.O.I.	Name, Vicinity, Phone Number, Address, Zip-Code, Coordinates, Previous, Favorites, User P.O.I.
Voice Guidance Language	3 Languages (Female): English (US), Spanish, French	3 Languages (Female): English (US), Spanish, French
Text-to-Speech	3 Languages (Female): English (US), Spanish, French	3 Languages (Female): English (US), Spanish, French
P.O.I.	Over 6 Million (infoUSA)	Over 6 Million (infoUSA)
Destination Memory	100 Favorites + Last 50 + 4 Via Points	100 Favorites + Last 50 + 4 Via Points
Route Calculation Options	✓ (Fastest/Shortest/Avoid Freeway, Ferry, Toll Road)	✓ (Fastest/Shortest/Avoid Freeway, Ferry, Toll Road)
Lane Guide	V	✓
Speed Limit Display	V	V
Magnified View	✓	✓
Quick Search	V	V
Max. Speed Alert	V	V
3 Types of Vehicle Position Icon	✓	V
P.O.I. Alert	V	V
Adaptive Volume Control	V	V
CD Player		
MP3/WMA/WAV Compatible with Tag	✓ (MP3/WAV Only)	✓ (MP3/WAV Only)
CD-R/RW Compatible	V	V
CD Text	V	V
DVD Player		
DVD-R/-RW, +R/+RW Compatible	✓	✓
Video DAC	108MHz/12-bit	108MHz/12-bit
GIGA MP3 MULTI	✓ (MP3 Only)	✓ (MP3 Only)
Dolby Digital	2 ch	2 ch
Frequency Response	16 - 22,000Hz (fs=48kHz) 16 - 44,000Hz (fs=96kHz)	16 - 22,000Hz (fs=48kHz) 16 - 44,000Hz (fs=96kHz)
Dynamic Range	93dB	93dB
Signal-to-Noise Ratio	95dB	95dB
Channel Separation	More than 85dB (at 1kHz)	More than 85dB (at 1kHz)
Wow & Flutter	Less than measurable limit	Less than measurable limit
Bluetooth Control*		
Bluetooth Control	Built-in	Built-in
Hands Free Call	V	V
Audio Streaming	V	V
Phone Book Access Profile	V	V
Phone Book Transfer	Manual (500 Max.)	Manual (500 Max.)
Mic Unit	V	V
* Available functions depend on cell phone.		
Pod/iPhone Control		
iPod Control	✓ (USB)	✓ (USB)
iPhone Control	✓ (USB)	✓ (USB)
Battery Charge	✓ (USB)	✓ (USB)
iPod/iPhone Video File Playback	V*2	V*2
2-Way Control for iPod/iPhone*1 (Headunit/iPod or iPhone Mode)	V*3	✓* 3
iTunes Tagging	V	V
	/iPhone differs by model. *2 KS-U29 required for iPod/iPhone vi	
	hone mode will pause your iPod/iPhone. For playback, please pr	ess "piay" on your iPod/iPhone.
USB	Front .	Freed
Position	Front	Front
MP3/WMA/WAV Compatible with Tag	✓ (MP3/WMA Only)	✓ (MP3/WMA Only)
iPod/iPhone Video Playback	✓ (AV Plug*)	✓ (AV Plug*)
iPod/iPhone Audio Playback	V	V

^{*} KS-U29 required for iPod/iPhone video playback. Compatibility depends on iPod.



Specifications

		KW-NT3HDT	KW-NT3HD
SD			
SD Slot		V	V
MP3/WMACompatible		V	V
Tuner			
HD Radio		Built-in	Built-in
SAT Radio Ready		V	V
Tuner Type		DiAS II	DiAS II
	esets (AM + FM)	6 + 18	6 + 18
AM	Frequency Range	40dB	40dB
	Sensitivity	530 - 1,710kHz	530 - 1,710kHz
	Selectivity	20μV	20μV
FM	Frequency Range	40dB	40dB
	Usable Sensitivity	87.5 - 107.9MHz	87.5 - 107.9MHz
	50dB Quieting Sensitivity	9.3dBf (0.8μV/75Ω)	9.3dBf (0.8μV/75Ω)
	Stereo Separation	16.3dBf (1.8μV/75Ω)	16.3dBf (1.8μV/75Ω)
	00 required		
Amplifier			
	n Power Output	50W x 4	50W x 4
CEA-2006	us Power Output (RMS) 6 Compliant ermonic Distortion	$20 + 20W$ RMS x 4CH at 4Ω $\leq 1\%$ THD* + N	$20 + 20W$ RMS x 4CH at 4Ω $\leq 1\%$ THD* + N
MOS-FET	Amp	V	V
Advanced	Multi-bit DAC	V	V
iEQ		7-band	7-band
HPF		V	V
AV Input		V	V
Video Input (Camera)		V	V
Line Pre-Output Terminals (Pair)		3	3
Subwoofer Output with Level/Frequency Control		V	V
Composite Video Output		V	V
Frequency Response		40 - 20,000Hz	40 - 20,000Hz
Load Impedance		4Ω (4 - 8Ω allowable)	4Ω (4 - 8Ω allowable)
Pre-Output Level/Impedance		2.5Vrms/20kΩ Load (CD full scale)	2.5Vrms/20kΩ Load (CD full scale)
Video Output		1.0Vp-p/75Ω	1.0Vp-p/75Ω
Video Input		1.0Vp-p/75Ω	1.0Vp-p/75Ω
Audio Inp	ut	1.5Vrms/20kΩ	1.5Vrms/20kΩ
Monitor			
Variable-0	Color Illumination	V	V
Touch Par	nel	V	V
TFT ON/O)FF	V	V
Multilingual Display		V*	V*
Screen Size		6.1" wide	6.1" wide
Number of Pixels		336,960	336,960
Color System		NTSC/PAL	NTSC/PAL
* English.	, Spanish, French		
General			
Detachable Control Panel		V	V
Carrying Case		V	V
Steering Wheel Remote Ready		V	V
Headunit		7 3/16" x 4 5/8" x 6 3/8" (182 x 111 x 161mm)	7 3/16" x 4 5/8" x 6 3/8" (182 x 111 x 161mm)
	Panel Size (W x H x D)	7 7/16" x 4 5/8" x 7/16" (188 x 117 x 10mm)	7 7/16" x 4 5/8" x 7/16" (188 x 117 x 10mm)
	Detachable Face Plate (W x H x D)	6 3/4" x 3 1/2" x 1 7/16" (170 x 88 x 36mm)	6 3/4" x 3 1/2" x 1 7/16" (170 x 88 x 36mm)
Weight		2.4 kg (5.3 lbs.)	2.4 kg (5.3 lbs.)