

# Specifications

## AV Receivers

	2-DIN AV Receivers		1-DIN AV Receiver	
	KW-AVX840	KW-AVX740	KW-AVX640	KW-AVX77
<b>CD Player</b>				
MP3/WMA/WAV Compatible with Tag	✓	✓	✓	✓
AAC Compatible*	✓	✓	✓	✓
JPEG/MPEG1, 2 Compatible	✓	✓	✓	✓
CD-R/RW Compatible	✓	✓	✓	✓
CD Text	✓	✓	✓	✓
* Not compatible with DRM-protected music purchased from iTunes Store.				
<b>DVD Player</b>				
DVD-R/-RW, +R/+RW Compatible	✓	✓	✓	✓
Video DAC	108MHz/12-bit	108MHz/12-bit	108MHz/12-bit	108MHz/12-bit
GIGA MP3 MULTI	✓	✓	✓	✓
AAC Compatible*	✓	✓	✓	✓
JPEG/MPEG1, 2 Compatible	✓	✓	✓	✓
DivX® Compatible	✓	✓	✓	✓
Dolby Pro Logic II	✓	✓	✓	✓
Dolby Digital	2 ch	2 ch	2 ch	5.1 ch
Dual-Zone	✓	✓	✓	✓
Video CD Playback	✓	✓	✓	✓
Frequency Response	16 - 22,000Hz (DVD fs=48/96kHz)	16 - 22,000Hz (DVD fs=48/96kHz)	16 - 22,000Hz (DVD fs=48/96kHz)	16 - 22,000Hz (DVD fs=48kHz) 16 - 44,000Hz (DVD fs=96kHz)
Dynamic Range	16 - 20,000Hz (CD fs=44.1kHz)	16 - 20,000Hz (CD fs=44.1kHz)	16 - 20,000Hz (CD fs=44.1kHz)	16 - 20,000Hz (CD)
Signal-to-Noise Ratio	93dB (fs=48kHz)	93dB (fs=48kHz)	93dB (fs=48kHz)	93dB (fs=48kHz)
Channel Separation	95dB (at 1kHz, fs=48kHz)	95dB (at 1kHz, fs=48kHz)	95dB (at 1kHz, fs=48kHz)	95dB (fs=48kHz)
Wow & Flutter	95dB (fs=48kHz)	95dB (fs=48kHz)	95dB (fs=48kHz)	95dB (at 1kHz, fs=48kHz)
Less than measureable limit				
* Not compatible with DRM-protected music purchased from iTunes Store.				
<b>Bluetooth Control*</b>				
Bluetooth Control	✓**	✓**	Ready**	✓
Compatibility Check Function	✓	✓	✓	✓
Hands Free Call	✓	✓	✓** (Redial)	✓
Audio Streaming & Control (A2DP1.2, AVRCP1.3)	✓	✓	✓**	✓
Text Message Display	✓**	✓**	✓**	✓**
Voice Recognition Dialing	✓	✓	✓**	✓
Phone Book Access Profile (PBAP1.0)	✓	✓	✓	✓
Phonebook Transfer	Manual (400 Max.)	Manual (400 Max.)	✓	Manual (100 Max.)
Mic Unit	✓	✓	✓**	✓
** Available functions depend on cell phone. ** Bluetooth Adapter included ** Receipt notification only ** KS-BTA100 required				
<b>iPod/iPhone Control*</b>				
iPod Control	✓ (USB)	✓ (USB)	✓ (USB)	✓ (USB/J-BUS*)
iPhone Control	✓ (USB)	✓ (USB)	✓ (USB)	✓ (USB)
Battery Charge	✓ (USB)	✓ (USB)	✓ (USB)	✓ (USB/J-BUS*)
iPod/iPhone Video File Playback	✓**	✓**	✓**	✓**
2-Way Control for iPod/iPhone*1 (Headunit/iPod or iPhone Mode)	✓ (USB)	✓ (USB)	✓ (USB)	✓ (USB)
External Mode for iPod/iPhone	✓ (USB)	✓ (USB)	✓ (USB)	✓ (USB)
*1 Compatibility with 2-way control for iPod/iPhone differs by model. ** KS-U30 required for iPod/iPhone video playback. Compatibility depends on iPod/iPhone. ** KS-PD100 required				
<b>USB</b>				
Position	Rear (Cable)	Rear (Cable)	Rear (Cable)	Rear (Cable)
MP3/WMA/WAV Compatible with Tag	✓	✓	✓	✓
AAC Compatible*	✓	✓	✓	✓
JPEG/MPEG1, 2 Compatible	✓	✓	✓	✓
DivX® Compatible**	✓	✓	✓	✓
iPod/iPhone Video Playback	✓ (AV Plug**)	✓ (AV Plug**)	✓ (AV Plug**)	✓ (AV Plug**)
iPod/iPhone Audio Playback	✓	✓	✓	✓
* Not compatible with DRM-protected music purchased from iTunes Store. ** DivX® files must be less than 2Mbps for playback on USB. ** KS-U30 required for iPod/iPhone video playback. Compatibility depends on iPod/iPhone.				
<b>Tuner</b>				
HD Radio	Ready*	Ready*	Ready*	Ready*
SAT Radio Ready	✓	✓	✓	✓
Tuner Type	HS-IVI	HS-IVI	HS-IVI	HS-IVI
No. of Presets (AM + FM)	6 + 18	6 + 18	6 + 18	6 + 18
<b>AM</b>				
Frequency Range	530 - 1,700kHz	530 - 1,700kHz	530 - 1,700kHz	530 - 1,710kHz
Sensitivity	20µV	20µV	20µV	20µV
Selectivity	40dB	40dB	40dB	40dB
<b>FM</b>				
Frequency Range	87.9 - 107.9MHz	87.9 - 107.9MHz	87.9 - 107.9MHz	87.5 - 107.9MHz
Usable Sensitivity	9.3dBf (0.8µV/75Ω)	9.3dBf (0.8µV/75Ω)	9.3dBf (0.8µV/75Ω)	9.3dBf (0.8µV/75Ω)
50dB Quieting Sensitivity	16.3dBf (1.8µV/75Ω)	16.3dBf (1.8µV/75Ω)	16.3dBf (1.8µV/75Ω)	16.3dBf (1.8µV/75Ω)
Stereo Separation	40dB	40dB	40dB	40dB
* KT-HD300 required				
<b>Amplifier</b>				
Maximum Power Output	50W x 4	50W x 4	50W x 4	50W x 4
Continuous Power Output (RMS)	20W RMS x 4CH at 4Ω ± 1.0% THD* + N	20W RMS x 4CH at 4Ω ± 1.0% THD* + N	20W RMS x 4CH at 4Ω ± 1.0% THD* + N	20W RMS x 4CH at 4Ω ± 1.0% THD* + N
CEA-2006 Compliant	✓	✓	✓	✓
* Total Harmonic Distortion				
MOS-FET Amp	✓	✓	✓	✓
Audio DAC	192kHz/24bit	192kHz/24bit	192kHz/24bit	192kHz/24bit
Parametric IEQ	3-band	3-band	3-band	7-band
IEQ	✓	✓	✓	✓
HPF	✓	✓	✓	✓
Headphone Surround	✓	✓	✓	✓
AV Input	✓	✓	✓	✓
Front AUX Input	✓	✓	✓	✓
Video Input (Camera)	✓	✓	✓	✓
Line Pre-Output Terminals	3 (Front + Rear + Subwoofer)	3 (Front + Rear + Subwoofer)	3 (Front + Rear + Subwoofer)	5* (Front + Rear + Subwoofer + 2nd Audio for Dual Zone)
Center Channel Output	✓	✓	✓	✓
Second Audio Output	✓	✓	✓	✓
Subwoofer Output with Level/Frequency Control	✓	✓	✓	✓
Composite Video Output	✓	✓	✓	✓
Frequency Response	40 - 20,000Hz	40 - 20,000Hz	40 - 20,000Hz	40 - 20,000Hz
Load Impedance	4Ω (4 - 8Ω allowable)	4Ω (4 - 8Ω allowable)	4Ω (4 - 8Ω allowable)	4Ω (4 - 8Ω allowable)
Pre-Output Level/Impedance	4.0V/20kΩ	4.0V/20kΩ	4.0V/20kΩ	5.0V/20kΩ
Video Output	1.0Vp-p/75Ω	1.0Vp-p/75Ω	1.0Vp-p/75Ω	1.0Vp-p/75Ω
Second Audio Output	1.1V/20kΩ	✓	✓	2.5V/20kΩ
Video Input	1.0Vp-p/75Ω	1.0Vp-p/75Ω	1.0Vp-p/75Ω	1.0Vp-p/75Ω
Audio Input	1.5V/20kΩ	1.5V/20kΩ	1.5V/20kΩ	1.5V/20kΩ
* Gold-Plated Terminals				
<b>Monitor</b>				
Proximity Sensor	✓	✓	✓	✓
Touch Panel	✓	✓	✓	✓
Variable-Color Illumination	✓	✓	✓	✓
TFT ON/OFF	✓	✓	✓	✓
Multilingual Display	✓	✓	✓	✓
Portuguese Display	✓	✓	✓	✓
Screen Size	7" wide	6.1" wide	6.1" wide	Ultra wide (5.4" wide)
Number of Pixels	1,152,000	1,152,000	1,152,000	576,000
Color System	NTSC/PAL	NTSC/PAL	NTSC/PAL	NTSC/PAL
* English, Spanish, French, German, Italian, Dutch, Portuguese, Swedish, Danish, Russian				
<b>General</b>				
Motorized Slide-Out Face	✓	✓	✓	✓
Detachable Control Panel	✓	✓	✓	✓
Carrying Case	✓	✓	✓	✓
Wireless Remote Control Type	Ready	Ready	Ready	Easy-Grip
Steering Wheel Remote Ready	✓	✓	✓	✓
<b>Headunit</b>				
Installation Size (W x H x D)	7 3/16" x 4 3/8" x 6 5/16" (182 x 111 x 160mm)	7 3/16" x 4 3/8" x 6 5/16" (182 x 111 x 160mm)	7 3/16" x 4 3/8" x 6 5/16" (182 x 111 x 160mm)	7 3/16" x 2 1/16" x 6 5/16" (182 x 52 x 160mm)
Panel Size (W x H x D)	7 7/16" x 4 5/8" x 7/16" (188 x 117 x 10mm)	7 7/16" x 4 5/8" x 7/16" (188 x 117 x 10mm)	7 7/16" x 4 5/8" x 7/16" (188 x 117 x 10mm)	7 7/16" x 2 5/16" x 1/2" (188 x 58 x 12mm)
Detachable Face Plate (W x H x D)	6 3/4" x 3 7/8" x 1 7/16" (171 x 97 x 35mm)	6 3/4" x 3 13/16" x 1 7/16" (171 x 96 x 35mm)	6 3/4" x 3 13/16" x 1 7/16" (171 x 96 x 35mm)	6 11/16" x 2 5/16" x 7/8" (169 x 58 x 22mm)
Weight	2.8kg (6.2 lbs.)	2.3kg (5.1 lbs.)	2.3kg (5.1 lbs.)	2.2kg (4.9 lbs.)

# Specifications

## CD Receivers

CD Player	2-DIN CD Receivers					1-DIN CD Receivers					
	KW-HDR720	KW-XR810	KW-XR610	KD-R820BT	KD-R720	KD-HDR70	KD-HDR44	KD-R620	KD-R520	KD-R420	KD-R320
MP3/WMA Compatible with ID3 Tag/WMA Tag	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
CD-R/RW Compatible	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
CD Text	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
Frequency Response	5 - 20,000Hz	5 - 20,000Hz	5 - 20,000Hz	5 - 20,000Hz	5 - 20,000Hz	5 - 20,000Hz	5 - 20,000Hz	5 - 20,000Hz	5 - 20,000Hz	5 - 20,000Hz	5 - 20,000Hz
Signal-to-Noise Ratio	98dB	102dB	98dB	102dB	102dB	98dB	98dB	98dB	98dB	98dB	98dB
Channel Separation	More than 85dB	More than 85dB	More than 85dB	More than 85dB	More than 85dB	More than 85dB	More than 85dB	More than 85dB	More than 85dB	More than 85dB	More than 85dB
Wow & Flutter	Less than measurable limit	Less than measurable limit	Less than measurable limit	Less than measurable limit	Less than measurable limit	Less than measurable limit	Less than measurable limit	Less than measurable limit	Less than measurable limit	Less than measurable limit	Less than measurable limit
<b>Bluetooth Control*</b>											
Bluetooth Control	Ready**2	✓**3	Ready**5	✓**3	✓**6	Ready**2	Ready**2	Ready**2	Ready**2	Ready**2	Ready**2
Compatibility Check Mode	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
Connects 2 Phones	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
Switching 2 Cell Phones	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
Hands Free Call	✓**2 (Redial)	✓	✓**5	✓	✓**6	✓**2 (Redial)	✓**2 (Redial)	✓**2 (Redial)	✓**2 (Redial)	✓**2 (Redial)	✓**2 (Redial)
Audio Streaming & Control (A2DP1.2, AVRCP1.3)	✓**2	✓	✓**5	✓	✓**6	✓**2	✓**2	✓**2	✓**2	✓**2	✓**2
Text Message Display	✓	✓**4	✓**3*4	✓**4	✓**4*6	✓	✓	✓	✓	✓	✓
Voice Recognition Dialing	✓**2	✓	✓**5	✓	✓**6	✓**2	✓**2	✓**2	✓**2	✓**2	✓**2
Phone Book Access Profile (PBAP1.0)	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
Phonebook Transfer	✓	✓	✓**5	✓	✓**6	✓	✓	✓	✓	✓	✓
Micro unit	✓**2	✓	✓**5	✓	✓**6	✓**2	✓**2	✓**2	✓**2	✓**2	✓**2
*1 Available functions depend on cell phone. **2 KS-BTA100 required **3 USB Bluetooth Adapter included **4 Receipt notification only **5 KS-BTA200 required **6 KS-BTA50 required											
<b>iPod/iPhone Control</b>											
iPod Control	✓ (USB)	✓ (USB)	✓ (USB)	✓ (USB)	✓ (USB)	✓ (USB)	✓ (USB)	✓ (USB)	✓ (USB)	✓ (USB)	✓ (USB)
iPhone Control	✓ (USB)	✓ (USB)	✓ (USB)	✓ (USB)	✓ (USB)	✓ (USB)	✓ (USB)	✓ (USB)	✓ (USB)	✓ (USB)	✓ (USB)
Battery Charge	✓ (USB)	✓ (USB)	✓ (USB)	✓ (USB)	✓ (USB)	✓ (USB)	✓ (USB)	✓ (USB)	✓ (USB)	✓ (USB)	✓ (USB)
2 Connections for iPod/iPhone	✓	✓ (USB)	✓ (USB)	✓ (USB)	✓ (USB)	✓ (USB)	✓ (USB)	✓ (USB)	✓ (USB)	✓ (USB)	✓ (USB)
2-Way Control for iPod/iPhone**1 (Headunit/iPod or iPhone Mode)	✓**2 (USB)	✓ (USB)	✓ (USB)	✓ (USB)	✓ (USB)	✓**2 (USB)	✓ (USB)	✓ (USB)	✓ (USB)	✓ (USB)	✓ (USB)
iTunes Tagging	✓ (USB)	✓ (USB)	✓ (USB)	✓ (USB/ Application Mode)	✓ (USB/ Application Mode)	✓ (USB)	✓ (USB)	✓ (USB)	✓ (USB)	✓ (USB)	✓ (USB)
External Mode for iPod/iPhone	✓ (USB)	✓ (USB)	✓ (USB)	✓ (USB/ Application Mode)	✓ (USB/ Application Mode)	✓ (USB)	✓ (USB)	✓ (USB)	✓ (USB)	✓ (USB)	✓ (USB)
*1 Compatibility with 2-Way Control for iPod/iPhone differs by model. **2 Switching from headunit mode to iPod/iPhone mode will pause your iPod/iPhone. For playback, please press "play" on your iPod/iPhone.											
<b>USB</b>											
Position	Front	Front/Rear	Front	Front/Rear	Front/Rear	Front		Front	Front	Front	
MP3/WMA Compatible with ID3 Tag/WMA Tag	✓	✓	✓	✓	✓	✓		✓	✓	✓	
WAV Compatible	✓	✓	✓	✓	✓	✓		✓	✓	✓	
iPod/iPhone Audio Playback	✓	✓	✓	✓	✓	✓		✓	✓	✓	
<b>Tuner</b>											
HD Radio	Built-in	Ready*	Ready*	Ready*	Ready*	Built-in	Built-in				
SAT Radio Ready	✓	✓	✓	✓	✓	✓	✓				
Tuner Type	DIAS II	HS-IVi	HS-IVi	HS-IVi	HS-IVi	DIAS II	DIAS II	HS-IVi	HS-IVi	HS-IVi	HS-IVi
No. of Presets (AM + FM)	6 + 18	6 + 18	6 + 18	6 + 18	6 + 18	6 + 18	6 + 18	6 + 18	6 + 18	6 + 18	6 + 18
<b>AM</b>											
Frequency Range	530 - 1,700kHz	530 - 1,710kHz	530 - 1,710kHz	530 - 1,700kHz	530 - 1,700kHz	530 - 1,700kHz	530 - 1,700kHz	530 - 1,700kHz	530 - 1,700kHz	530 - 1,700kHz	530 - 1,700kHz
Sensitivity	20µV	20µV	20µV	20µV	20µV	20µV	20µV	20µV	20µV	20µV	20µV
Selectivity	70dB	40dB	40dB	40dB	40dB	70dB	70dB	40dB	40dB	40dB	40dB
<b>FM</b>											
Frequency Range	87.9 - 107.9MHz	87.5 - 107.9MHz	87.5 - 107.9MHz	87.9 - 107.9MHz	87.9 - 107.9MHz	87.9 - 107.9MHz	87.9 - 107.9MHz	87.9 - 107.9MHz	87.9 - 107.9MHz	87.9 - 107.9MHz	87.9 - 107.9MHz
Usable Sensitivity	11.3dBf (1µV/75Ω)	9.3dBf (0.8µV/75Ω)	9.3dBf (0.8µV/75Ω)	9.3dBf (0.8µV/75Ω)	9.3dBf (0.8µV/75Ω)	11.3dBf (1µV/75Ω)	11.3dBf (1µV/75Ω)	9.3dBf (0.8µV/75Ω)	9.3dBf (0.8µV/75Ω)	9.3dBf (0.8µV/75Ω)	9.3dBf (0.8µV/75Ω)
50dB Quieting Sensitivity	19.3dBf (2.5µV/75Ω)	16.3dBf (1.8µV/75Ω)	16.3dBf (1.8µV/75Ω)	16.3dBf (1.8µV/75Ω)	16.3dBf (1.8µV/75Ω)	19.3dBf (2.5µV/75Ω)	19.3dBf (2.5µV/75Ω)	16.3dBf (1.8µV/75Ω)	16.3dBf (1.8µV/75Ω)	16.3dBf (1.8µV/75Ω)	16.3dBf (1.8µV/75Ω)
Stereo Separation	48dB	40dB	40dB	40dB	40dB	48dB	48dB	40dB	40dB	40dB	40dB
* KT-HD300 required											
<b>Amplifier</b>											
Maximum Power Output	50W x 4	50W x 4	50W x 4	50W x 4	50W x 4	50W x 4	50W x 4	50W x 4	50W x 4	50W x 4	50W x 4
Continuous Power Output (RMS) CEA-2006 Compliant	20W RMS x 4CH at 4Ω ≤ 1.0% THD* + N	20W RMS x 4CH at 4Ω ≤ 1.0% THD* + N	20W RMS x 4CH at 4Ω ≤ 1.0% THD* + N	20W RMS x 4CH at 4Ω ≤ 1.0% THD* + N	20W RMS x 4CH at 4Ω ≤ 1.0% THD* + N	20W RMS x 4CH at 4Ω ≤ 1.0% THD* + N	20W RMS x 4CH at 4Ω ≤ 1.0% THD* + N	20W RMS x 4CH at 4Ω ≤ 1.0% THD* + N	20W RMS x 4CH at 4Ω ≤ 1.0% THD* + N	20W RMS x 4CH at 4Ω ≤ 1.0% THD* + N	20W RMS x 4CH at 4Ω ≤ 1.0% THD* + N
* Total Harmonic Distortion	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
MODS-FET Amp	✓	✓**1	✓	✓	✓**1	✓	✓	✓	✓	✓	✓
24-bit DAC	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
Loudness Control	✓	✓ (3 patterns)	✓	✓	✓	✓	✓	✓	✓	✓	✓
Parametric IEQ	3-band	3-band	3-band	3-band	3-band	3-band	3-band	3-band	3-band	3-band	3-band
HPF	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
Line Pre-Output Terminals	3 (Front + Rear + Subwoofer)	3 (Front + Rear + Subwoofer)	2**2 (Front + Rear/Subwoofer)	3 (Front + Rear + Subwoofer)	2**2 (Front + Rear/Subwoofer)	3 (Front + Rear + Subwoofer)	2**2 (Front + Rear/Subwoofer)	2**2 (Front + Rear/Subwoofer)	2**2 (Front + Rear/Subwoofer)	1**2 (Rear/Subwoofer)	1**2 (Rear/Subwoofer)
Subwoofer Output with Level/Frequency Control	✓	✓**2	✓**2	✓**2	✓**2	✓**2	✓**2	✓**2	✓**2	✓**2	✓**2
AUX Input	2 (Front/Rear)	1 (Front)	1 (Front)	1 (Front)	1 (Front)	2 (Front/Rear)	2 (Front/Rear)	2 (Front/Rear)	2 (Front/Rear)	2 (Front/Rear)	2 (Front/Rear)
Load Impedance	4Ω (4 - 8Ω allowable)	4Ω (4 - 8Ω allowable)	4Ω (4 - 8Ω allowable)	4Ω (4 - 8Ω allowable)	4Ω (4 - 8Ω allowable)	4Ω (4 - 8Ω allowable)	4Ω (4 - 8Ω allowable)	4Ω (4 - 8Ω allowable)	4Ω (4 - 8Ω allowable)	4Ω (4 - 8Ω allowable)	4Ω (4 - 8Ω allowable)
Line Pre-Output Level	2.5V	2.5V	2.5V	2.5V	2.5V	2.5V	2.5V	2.5V	2.5V	2.5V	2.5V
Line Pre-Output Impedance	Less than 600Ω	1kΩ	1kΩ	Less than 600Ω	Less than 600Ω	Less than 600Ω	Less than 600Ω	Less than 600Ω	Less than 600Ω	Less than 600Ω	Less than 600Ω
*1 TV/Burr-Brown **2 Rear/Subwoofer Selectable											
<b>Display</b>											
Separated Variable-Color	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
Full Dot LCD	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
Dimmer	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
<b>General</b>											
Detachable Control Panel	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
Carrying Case	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
Beep Tone Support	✓**	✓	✓**	✓**	✓**	✓**	✓**	✓**	✓**	✓**	✓**
Wireless Remote Control Type	Oval-Shaped	Oval-Shaped	Oval-Shaped	Oval-Shaped	Oval-Shaped	Oval-Shaped	Oval-Shaped	Oval-Shaped	Oval-Shaped	Oval-Shaped	Oval-Shaped
Rotary Encoder	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
Steering Wheel Remote Ready	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
<b>Headunit</b>											
Installation Size (W x H x D)	7 3/16" x 4 3/8" x 6 5/16" (182 x 111 x 159.5mm)	7 3/16" x 4 3/8" x 6 5/16" (182 x 111 x 159.5mm)	7 3/16" x 4 3/8" x 6 5/16" (182 x 111 x 159.5mm)	7 3/16" x 2 1/16" x 6 1/4" (182 x 52 x 158mm)	7 3/16" x 2 1/16" x 6 1/4" (182 x 52 x 158mm)	7 3/16" x 2 1/16" x 6 1/4" (182 x 52 x 158mm)	7 3/16" x 2 1/16" x 6 5/16" (182 x 52 x 159mm)	7 3/16" x 2 1/16" x 6 5/16" (182 x 52 x 159mm)	7 3/16" x 2 1/16" x 6 5/16" (182 x 52 x 159mm)	7 3/16" x 2 1/16" x 6 5/16" (182 x 52 x 159mm)	7 3/16" x 2 1/16" x 6 5/16" (182 x 52 x 159mm)
Panel Size (W x H x D)	7 7/16" x 6 5/8" x 15/16" (188 x 116.8 x 22.5mm)	7 7/16" x 6 5/8" x 15/16" (188 x 116.8 x 22.5mm)	7 7/16" x 6 5/8" x 15/16" (188 x 116.8 x 22.5mm)	7 7/16" x 2 3/8" x 3 3/8" (188 x 59 x 8.5mm)	7 7/16" x 2 3/8" x 3 3/8" (188 x 59 x 8.5mm)	7 7/16" x 2 3/8" x 3 3/8" (188 x 59 x 8.5mm)	7 7/16" x 2 3/8" x 3 3/8" (188 x 59 x 8.5mm)	7 7/16" x 2 3/8" x 3 3/8" (188 x 59 x 8.5mm)	7 7/16" x 2 3/8" x 3 3/8" (188 x 59 x 8.5mm)	7 7/16" x 2 3/8" x 3 3/8" (188 x 59 x 8.5mm)	7 7/16" x 2 3/8" x 3 3/8" (188 x 59 x 8.5mm)
Detachable Face Plate (W x H x D)				6 3/4" x 1 13/16" x 7/8" (170 x 46.4 x 20.5mm)	6 3/4" x 1 13/16" x 7/8" (170 x 46.4 x 20.5mm)	6 3/4" x 1 13/16" x 7/8" (170 x 46.4 x 20.5mm)	6 3/4" x 1 13/16" x 7/8" (170 x 46.4 x 21.1mm)	6 3/4" x 1 13/16" x 7/8" (170 x 46.4 x 20.5mm)	6 3/4" x 1 13/16" x 7/8" (170 x 46.4 x 20.6mm)	6 3/4" x 1 13/16" x 7/8" (170 x 46.4 x 21.1mm)	6 3/4" x 1 13/16" x 7/8" (170 x 46.4 x 21.1mm)
Weight	1.81kg (4.0 lbs.)	1.9kg (4.2 lbs.)	1.8kg (4.0 lbs.)	1.3kg (2.9 lbs.)	1.3kg (2.9 lbs.)	1.27kg (2.79 lbs.)	1.23kg (2.75 lbs.)	1.21kg (2.7 lbs.)	1.21kg (2.7 lbs.)	1.21kg (2.7 lbs.)	1.23kg (2.75 lbs.)
* From Speakers											