## **Specifications**

## AV Navigation Systems

| Navigation System   |  |  |
|---|--|--|
| Туре  | On-Board Flash Memory Based Navigation System  | On-Board Flash Memory Based Navigation System  |
| GPS   | ✓ (WAAS Capable)   | ✓ (WAAS Capable)   |
| Speed Pulse   |  |  |
| Gyro Sensor   | K.   | ×  |
| Coverage  | United States, Alaska, Hawaii, Canada, and Puerto Rico   | United States, Alaska, Hawaii, Canada, and Puerto Rice   |
| StreetDirector Assistant  |  | V  |
| HD Radio® Traffic & News Service                                  |  | V  |
|   |  | Neme Visinity Dhone Number Address Zin Code  |
| Destination Search Functions                                      | Name, Vicinity, Phone Number, Address, Zip-Code,<br>Coordinates, Previous, Favorites, User POI                     | Name, Vicinity, Phone Number, Address, Zip-Code,<br>Coordinates, Previous, Favorites, User POI |
| Voice Guidance Language   | 3 Languages (Female): English (US), Spanish, French  | 3 Languages (Female): English (US), Spanish, French  |
| Text-to-Speech  | 3 Languages (Female): English (US), Spanish, French  | 3 Languages (Female): English (US), Spanish, French  |
| POI   | Over 6 Million (infoUSA)   | Over 6 Million (infoUSA)   |
| Destination Memory  | 100 Favorites + Last 50 + 4 Via Points   | 100 Favorites + Last 50 + 4 Via Points   |
| Route Calculation Options   | ✓ (Fastest/Shortest/Avoid Freeway, Ferry, Toll Road)   | ✓ (Fastest/Shortest/Avoid Freeway, Ferry, Toll Road)   |
| Lane Guide  | V  | V  |
| Speed Limit Display   | V  | V  |
| Magnified View  | V  | V  |
| Quick Search  | K.   | ×  |
| Max. Speed Alert  | V  | Y  |
| 3 Types of Vehicle Position Icon                                  |  | V<br>V   |
| POI Alert   |  |  |
|   |  |  |
| Adaptive Volume Control   | V  | V  |
| CD Player   |  |  |
| MP3/WMA/WAV Compatible with Tag                                   | ✓ (MP3/WAV Only)   | ✓ (MP3/WAV Only)   |
| CD-R/RW Compatible  | V  | V  |
| CD Text   | V  | V  |
| OVD Player  |  |  |
| DVD-R/-RW, +R/+RW Compatible                                      | V  | V  |
| Video DAC   | 108MHz/12-bit  | 108MHz/12-bit  |
| GIGA MP3 MULTI  | V (MP3 Only)   | V (MP3 Only)   |
| Dolby Digital   | 2 ch   | 2 ch   |
| Frequency Response  | 16 - 20,000Hz (fs=48kHz/96kHz)   | 16 - 20,000Hz (fs=48kHz/96kHz)   |
| Dynamic Range   | 93dB   | 93dB   |
| , ,   |  |  |
| Signal-to-Noise Ratio   | 95dB   | 95dB   |
| Channel Separation  | More than 85dB (at 1kHz)   | More than 85dB (at 1kHz)   |
| Wow & Flutter   | Less than measurable limit   | Less than measurable limit   |
| Bluetooth Control*  | 1  |  |
| Bluetooth Control   | Built-in   | Built-in   |
| Hands Free Call   | V  | V  |
| Audio Streaming & Control (A2DP1.2, AVRCP1.3                      | ) 🗸  | V  |
| Phone Book Access Profile (PBAP1.0)                               | V  | V  |
| Phone Book Transfer   | Manual (500 Max.)  | Manual (500 Max.)  |
| Mic Unit  | V  | V  |
| * Available functions depend on cell phone.                       |  | -  |
| Pod/iPhone Control  |  |  |
| iPod Control  | ✓ (USB)  | ✔ (USB)  |
| iPhone Control  | ✓ (USB)  | ✓ (USB)  |
|   |  |  |
| Battery Charge  | ✓ (USB)  | ✓ (USB)  |
| iPod/iPhone Video File Playback                                   | V*2  | V*2  |
| 2-Way Control for iPod/iPhone*1<br>(Headunit/iPod or iPhone Mode) | ✓*3 (USB)  | ✔*3 (USB)  |
| External Mode for iPod/iPhone                                     | ✓ (USB)  | ✓ (USB)  |
| iTunes Tagging  | V (USB)  | V (USB)  |
| *1 Compatibility with 2-way control for iPod/iPho                 | one differs by model. *2 KS-U39 required for iPod/iPhone vide will pause your iPod/iPhone. For playback, please pr | deo playback. Compatibility depends on iPod/iPhone.  |
| ISB   | , , , , , , , , , , , , , , , , , , ,  |  |
|   | Front  | Front  |
|   | 1 HORE   |  |
| Position  | A (MD2/M/MA Only)  | A (MD2 (MMA Only)  |
| MP3/WMA/WAV Compatible with Tag                                   | ✓ (MP3/WMA Only)   | ✓ (MP3/WMA Only)   |
|   | ✓ (MP3/WMA Only)<br>✓ (AV Plug*)<br>✓  | ✓ (MP3/WMA Only)<br>✓ (AV Plug*)   |

iPod/iPhone Audio Playback ✓ \* KS-U39 required for iPod/iPhone video playback. Compatibility depends on iPod.

## Specifications

|  |                                   | KW-NT50HDT   | KW-NT30HD  |
|--|-----------------------------------|--|--|
| SD   |                                   |  |  |
| SD Slot  |                                   | V  | V  |
| MP3/WMACompatible  |                                   | V  | V  |
| Tuner  |                                   |  |  |
| HD Radio   |                                   | Built-in   | Built-in   |
| SAT Radio Ready  |                                   | V  | V  |
| Tuner Type   |                                   | DiRaNa   | DiRaNa   |
|  | sets (AM + FM)                    | 6 + 18   | 6 + 18   |
| AM   | Frequency Range                   | 530 - 1,710kHz   | 530 - 1,710kHz   |
|  | Sensitivity                       | 13µV   | 13µV   |
|  | Selectivity                       | 80dB   | 80dB   |
| FM   | Frequency Range                   | 87.5 - 107.9MHz  | 87.5 - 107.9MHz  |
|  | Usable Sensitivity                | 8.3dBf (0.7μV/75Ω)   | 8.3dBf (0.7μV/75Ω)   |
|  | 50dB Quieting Sensitivity         | 14.3dBf (1.4μV/75Ω)  | 14.3dBf (1.4μV/75Ω)  |
|  | Stereo Separation                 | 70dB (HD Radio Broadcast)  | 70dB (HD Radio Broadcast)  |
|  |                                   | 50dB (Conventional Broadcast)  | 50dB (Conventional Broadcast)  |
| Amplifier  |                                   |  |  |
| Maximum Power Output   |                                   | 50W x 4  | 50W x 4  |
| Continuous Power Output (RMS)<br>CEA-2006 Compliant<br>* Total Harmonic Distortion |                                   | $\begin{array}{l} 20 + 20W \text{ RMS x 4CH at } 4\Omega \\ \leqq 1\% \text{ THD}^* + N \end{array}$ | $\begin{array}{l} 20 + 20W \mbox{ RMS x 4CH at } 4\Omega \\ \leqq 1\% \mbox{ THD}^* + N \end{array}$ |
| MOS-FET A  | Amp                               | V  | V  |
| Advanced I   | Multi-bit DAC                     | V  | V  |
| iEQ  |                                   | 7-band   | 7-band   |
| HPF  |                                   | V  | V  |
| AV Input   |                                   | V  | V  |
| Front AUX Input  |                                   | V  | V  |
| Video Input (Camera)   |                                   | V  | V  |
| Line Pre-Output Terminals  |                                   | 3 (Front + Rear + Subwoofer)   | 3 (Front + Rear + Subwoofer)   |
| Subwoofer Output with Level/Frequency Control                                      |                                   | V  | V  |
| Composite Video Output   |                                   | V  | V  |
| Frequency Response   |                                   | 40 - 20,000Hz  | 40 - 20,000Hz  |
| Load Impedance   |                                   | 4Ω (4 - 8Ω allowable)  | 4Ω (4 - 8Ω allowable)  |
| Pre-Output Level/Impedance   |                                   | 2.5Vrms/20kΩ Load (CD full scale)  | 2.5Vrms/20kΩ Load (CD full scale)  |
| Video Output   |                                   | 1.0Vp-p/75Ω  | 1.0Vp-p/75Ω  |
| Video Input  |                                   | 1.0Vp-p/75Ω  | 1.0Vp-p/75Ω  |
| Audio Input  |                                   | 0.5Vrms/20kΩ   | 0.5Vrms/20kΩ   |
| Monitor  |                                   |  |  |
| Variable-Color Illumination  |                                   | V  | V  |
| Touch Panel  |                                   | V  | V  |
| TFT ON/OFF   |                                   | V  | V  |
| Multilingual Display   |                                   | V*   | V*   |
| Screen Size  |                                   | 6.1" wide  | 6.1" wide  |
| Number of Pixels   |                                   | 336,960  | 336,960  |
| Color System   |                                   | NTSC/PAL   | NTSC/PAL   |
|  | Spanish, French                   |  |  |
| General  | ·                                 |  |  |
| Detachable Control Panel   |                                   | V  | V  |
| Carrying Case  |                                   | V  | V  |
| Steering Wheel Remote Ready  |                                   | V  | V  |
| Headunit   | Installation Size (W x H x D)     | 7 3/16" x 4 5/8" x 6 3/8" (182 x 111 x 161mm)  | 7 3/16" x 4 5/8" x 6 3/8" (182 x 111 x 161mm)  |
|  | Panel Size (W x H x D)            | 7 7/16" x 4 5/8" x 7/16" (188 x 117 x 10mm)  | 7 7/16" x 4 5/8" x 7/16" (188 x 117 x 10mm)  |
|  | Detachable Face Plate (W x H x D) | 6 3/4" x 3 1/2" x 1 7/16" (170 x 88 x 36mm)  | 6 3/4" x 3 1/2" x 1 7/16" (170 x 88 x 36mm)  |
| Weight   |                                   | ( · · · · · · · · · · · · · · · · · · ·  | ( · · · · · · · · · · · · · · · · · · ·  |